

Reducers



Reducer Grooved



Reducer Threaded



Reducer Exentric Grooved

Normal Size mm-inch	(D) Pipe O.D. mm-inch	Working Pressure Bar/PSI	(L) Length and (d) Ø Diamter in mm-inch					
			Reducer Grooved		Reducer Threaded		Reducer Exentric Grooved	
			length	diameter	length	diameter	length	diameter
1¼ x 1"	42,4-1.669"	27,5/400	64-2.519"	33,7-1.327"				
1½ x 1"	48,3-1.900"	27,5/400	64-2.519"	33,7-1.327"				
1½ x 1¼"	48,3-1.900"	27,5/400	64-2.519"	42,4-1.669"				
2 x 1"	60,3-2.375"	27,5/400	64-2.519"	33,7-1.327"		33,7-1.327"		
2 x 1¼"	60,3-2.375"	27,5/400	64-2.519"	42,4-1.669"		42,4-1.669"		
2 x 1½"	60,3-2.375"	27,5/400	64-2.519"	48,3-1.900"	64-2.519"	48,3-1.900"		
2½ x 1"	73,0-2.875"	27,5/400	64-2.519"	33,7-1.327"	64-2.519"	33,7-1.327"		
2½ x 1¼"	73,0-2.875"	27,5/400	64-2.519"	42,4-1.669"	64-2.519"	42,4-1.669"		
2½ x 1½"	73,0-2.875"	27,5/400	64-2.519"	48,3-1.900"	64-2.519"	48,3-1.900"		
2½ x 2"	73,0-2.875"	27,5/400	64-2.519"	60,3-2.375"	64-2.519"	60,3-2.375"		
2½ x 1"	76,1-3.000"	27,5/400	64-2.519"	33,7-1.327"	64-2.519"	33,7-1.327"		
2½ x 1¼"	76,1-3.000"	27,5/400	64-2.519"	42,4-1.669"	64-2.519"	42,4-1.669"		
2½ x 1½"	76,1-3.000"	27,5/400	64-2.519"	48,3-1.900"	64-2.519"	48,3-1.900"		
2½ x 2"	76,1-3.000"	27,5/400	64-2.519"	60,3-2.375"	64-2.519"	60,3-2.375"		
3 x 1"	88,9-3,500"	27,5/400	64-2.519"	33,7-1.327"	64-2.519"	33,7-1.327"		
3 x 1¼"	88,9-3,500"	27,5/400	64-2.519"	42,4-1.669"	64-2.519"	42,4-1.669"		
3 x 1½"	88,9-3,500"	27,5/400	64-2.519"	48,3-1.900"	64-2.519"	48,3-1.900"		
3 x 2"	88,9-3,500"	27,5/400	64-2.519"	60,3-2.375"	64-2.519"	60,3-2.375"	64-2.519"	60,3-2.375"
3 x 2½"	88,9-3,500"	27,5/400	64-2.519"	73,0-2.875"	64-2.519"	73,0-2.875"		
3 x 2½"	88,9-3,500"	27,5/400	64-2.519"	76,1-3.000"	64-2.519"	76,1-3.000"	64-2.519"	76,1-3.000"
4 x 1"	114,3-4.500"	27,5/400				33,7-1.327"		
4 x 1½"	114,3-4.500"	27,5/400	76,1-3.000"	48,3-1.900"	76,1-3.000"	48,3-1.900"		
4 x 2"	114,3-4.500"	27,5/400	76,1-3.000"	60,3-2.375"	76,1-3.000"	60,3-2.375"	76,1-3.000"	48,3-1.900"
4 x 2½"	114,3-4.500"	27,5/400	76,1-3.000"	73,0-2.875"	76,1-3.000"	73,0-2.875"	76,1-3.000"	73,0-2.875"
4 x 2½"	114,3-4.500"	27,5/400	76,1-3.000"	76,1-3.000"	76,1-3.000"	76,1-3.000"	76,1-3.000"	76,1-3.000"
4 x 3"	114,3-4.500"	27,5/400	76,1-3.000"	88,9-3,500"			76,1-3.000"	88,9-3,500"
5 x 1"	139,7-5.500"	27,5/400			88,9-3,500"	33,7-1.327"		
5 x 1¼"	139,7-5.500"	27,5/400			88,9-3,500"	42,4-1.669"		
5 x 1½"	139,7-5.500"	27,5/400			88,9-3,500"	48,3-1.900"		
5 x 2"	139,7-5.500"	27,5/400	88,9-3,500"	60,3-2.375"	88,9-3,500"	60,3-2.375"		
5 x 2½"	139,7-5.500"	27,5/400	88,9-3,500"	76,1-3.000"	88,9-3,500"	76,1-3.000"	88,9-3,500"	76,1-3.000"
5 x 3"	139,7-5.500"	27,5/400	88,9-3,500"	88,9-3,500"	88,9-3,500"	88,9-3,500"	88,9-3,500"	88,9-3,500"
5 x 4"	139,7-5.500"	27,5/400	88,9-3,500"	114,3-4.500"			88,9-3,500"	114,3-4.500"
6 x 1"	165,1-6.500"	27,5/400			101,5-3.996"	33,7-1.327"		
6 x 1¼"	165,1-6.500"	27,5/400			101,5-3.996"	42,4-1.669"		
6 x 1½"	165,1-6.500"	27,5/400			101,5-3.996"	48,3-1.900"		
6 x 2"	165,1-6.500"	27,5/400	101,5-3.996"	60,3-2.375"	101,5-3.996"	60,3-2.375"		
6 x 2½"	165,1-6.500"	27,5/400	101,5-3.996"	76,1-3.000"	101,5-3.996"	76,1-3.000"		76,1-3.000"
6 x 3"	165,1-6.500"	27,5/400	101,5-3.996"	88,9-3,500"	101,5-3.996"	88,9-3,500"		88,9-3,500"
6 x 4"	165,1-6.500"	27,5/400	101,5-3.996"	114,3-4.500"	101,5-3.996"	114,3-4.500"		114,3-4.500"
6 x 5"	165,1-6.500"	27,5/400	101,5-3.996"	139,7-5.500"				139,7-5.500"
6 x 1"	168,3-6.625"	27,5/400			101,5-3.996"	33,7-1.327"		
6 x 2"	168,3-6.625"	27,5/400	101,5-3.996"	60,3-2.375"	101,5-3.996"	60,3-2.375"		
6 x 2½"	168,3-6.625"	27,5/400	101,5-3.996"	73,0-2.875"				
6 x 2½"	168,3-6.625"	27,5/400	101,5-3.996"	76,1-3.000"				

Reducers



Reducer Grooved



Reducer Threaded



Reducer Exentric Grooved

Normal Size mm-inch	(D) Pipe O.D. mm-inch	Working Pressure Bar/PSI	(L) Length and (d) Ø Diamter in mm-inch					
			Reducer Grooved		Reducer Threaded		Reducer Exentric Grooved	
			length	diameter	length	diameter	length	diameter
6 x 3"	168,3-6.625"	27,5/400	101,5-3.996"	88,9-3,500"			101,5-3.996"	88,9-3,500"
6 x 4"	168,3-6.625"	27,5/400	101,5-3.996"	114,3-4.500"	101,5-3.996"	114,3-4.500"	101,5-3.996"	114,3-4.500"
6 x 5"	168,3-6.625"	27,5/400	101,5-3.996"	139,7-5.500"			101,5-3.996"	139,7-5.500"
8 x 2"	219,1-8.625"	27,5/400				60,3-2.375"		
8 x 2½"	219,1-8.625"	27,5/400	127-5.000"	73,0-2.875"				
8 x 2½"	219,1-8.625"	20,7/300	127-5.000"	76,1-3.000"	127-5.000"	76,1-3.000"		
8 x 3"	219,1-8.625"	20,7/300	127-5.000"	88,9-3,500"	127-5.000"	88,9-3,500"	127-5.000"	88,9-3,500"
8 x 4"	219,1-8.625"	20,7/300	127-5.000"	114,3-4.500"			127-5.000"	114,3-4.500"
8 x 5"	219,1-8.625"	20,7/300	127-5.000"	139,7-5.500"			127-5.000"	139,7-5.500"
8 x 6"	219,1-8.625"	20,7/300	127-5.000"	165,1-6.500"			127-5.000"	165,1-6.500"
8 x 6"	219,1-8.625"	20,7/300	127-5.000"	168,3-6.625"			127-5.000"	168,3-6.625"
10 x 4"	273,0-10,784"	20,7/300	140-5.511"	114,3-4.500"				
10 x 6"	273,0-10,784"	20,7/300	140-5.511"	165,1-6.500"			140-5.511"	165,1-6.500"
10 x 6"	273,0-10,784"	20,7/300	140-5.511"	168,3-6.625"			140-5.511"	168,3-6.625"
10 x 8"	273,0-10,784"	20,7/300	140-5.511"	219,1-8.625"			140-5.511"	219,1-8.625"